

MODULATING ULTRA FORCE™ SUF/SUFL COMMON VENTING KIT

BENEFITS

- Fewer wall penetrations than standard single-unit venting
- Reduced install cost with easy to install non-powered kits
- Flexibility of using PVC or polypropylene vent material

SPECIFICATIONS

- Approved for use with 120, 150, 199, 250, 300, 400 and 500 Modulating Ultra Force™ models and SUFL 150, 199, 250, 300, 400 and 500
- Approved for side wall (horizontal) vent applications only
- 50 Feet maximum equivalent length of straight pipe common vent and elbows

- Direct vent configuration only
- Maximum of three water heaters can be common vented
- One kit per water heater required, chose from PVC or polypropylene, model input size
- Kits include backflow preventer plus intake and exhaust adapters. Piping and termination field supplied.
- Each wall penetration requires a 7" hole through the structure
- Common vent kits are UL listed



SOLID. STATE.





Commercial Gas

Accessories

Part Numbers	Description
100227396	PVC Common Vent Kit, 120 – 250 Models
100223775	PVC Common Vent Kit, 300 – 500 Models
100227395	Polypropylene Common Vent Kit, 120 -250 Models
100223774	Polypropylene Common Vent Kit, 300 - 500 Models

Installations must comply with all national, state and local codes.
See kit instructions and corresponding water heater manual for detailed installation instructions and additional information.

FOR MORE INFORMATION ON CALL 1-800-365-0024. STATE WATER HEATERS RESERVES THE RIGHT TO MAKE PRODUCT CHANGES OR IMPROVEMENTS WITHOUT PRIOR NOTICE.